

**TECHNICAL DATA, ARISTO® MIG 4004i PULSE**

Mains Voltage, V	380-460
Number of Phases, ph	3
Supply Frequency, Hz	50/60
Fuse Slow, A	20
<b>Welding Output A/V</b>	
100% duty cycle	300/29
60% duty cycle	400/34
<b>Setting range A</b>	
MIG/MAG	16-400
MMA	16-400
TIG	4-400
Open Circuit Voltage, V	55
Open Circuit Voltage VRD, V	<35
Rated kVA	25.2
Energy Save Mode, W	40
Efficiency at Max Current %	89.5
Power Factor at Max Current	0.95
Dimensions L x W x H, mm	610 x 250 x 445
Weight with / without COOL 1, kg	58/44.5
Operating Temperature, °C	-10 to +40
Enclosure Class	IP23
Application Class	S
Insulation Class	H
Certification Mark (Standards)	CE
Recommended Mains Cable Cross Section	AWG 10, (4x 4,0 mm <sup>2</sup> )

**TECHNICAL DATA, WATER COOLER COOL 1**

Power supply, from power source, VDC	24
Coolant flow capacity, l/min	2.0
Coolant quantity, l	4.5
Cooling power, kW	1.3
Max pressure, bar	4.5
Max pressure height to torch, m	8.5
Weight / incl. coolant, kg	12/16.5
Dimensions incl. filler tube L x W x H, mm	610 x 256 x 256

**TECHNICAL DATA, ARISTO® FEED 3004**

Power supply, AC	42
Wire spool capacity, kg	18 (30**)
Max. spool diameter, mm	300 (440**)
Wire feed speed, m/min	0.8-25.0
Dimension L x W x H, mm	690 x 275 x 420
Weight, kg	15

**ORDERING INFORMATION: TYPICAL PLANT, W1009640**

Aristo Mig 4004i Pulse 380-440	0465152881
Trolley 4Wheel-AristoMig 4004i	0462151880
Kit Bracket-Trolley Mig 4004i	0463125880
Aristo Feed 3004W MO	0460526891
Aristo Pendant U82 Plus Incl Holder	0460820881
PSF405 L=3m Euro	0458401882
Con. Set AA 10m Can 70mm 2 10p	0459528782
REG COMET 250 ARG 45LPM 2GA	201017
KIT CONN 5/8UNRH-5MM HOSE	308689

U82 Super Pulse and Water Cooled versions available.

**ORDERING INFORMATION, POWER SOURCE, FEEDERS ARISTO, ARISTO® U82**

<b>Power Source</b>	
Aristo® Mig 4004i Pulse	0465 152 884
<b>Aristo® U82</b>	<b>Air/Water-Cooled</b>
Aristo® U82 Plus complete incl. holder	0460 820 881
Control cable extension U82 7.5 m	0460 877 891

**ORDERING INFORMATION, INTERCONNECTION CABLES**

70 mm <sup>2</sup> Feed 3004	Air-Cooled	Water-Cooled
1.7 m, 10 pole	0459 528 780	0459 528 790
5.0 m, 10 pole	0459 528 781	0459 528 791
10.0 m, 10 pole	0459 528 782	0459 528 792
15.0 m, 10 pole	0459 528 783	0459 528 793
25.0 m, 10 pole	0459 528 784	0459 528 794
35.0 m, 10 pole	0459 528 785	0459 528 795

**ORDERING INFORMATION, ACCESSORIES**

Wheel kit for feeder	0458 707 880
Strain relief for welding torch	0457 341 881
Strain relief for interconnection cables	0459 234 880
Lifting eye	0458 706 880
Quick connector MarathonPac™	F102 440 880
Adapter for 5 kg spool	0455 410 001
Spool cover	0458 674 880
Spool cover, steel	0459 431 880
Adapter for spool diameter 440 mm	0459 233 880**
Remote control MTA1 CAN	0459 491 880
Remote control MT1 10Prog CAN	0459 491 882
Remote interconn. cable MTA1 and M1 10Prog, 5 m	0459 960 880
Remote adapter kit Miggy-/Railtrac	0459 681 880
Remote adapter kit MXH™ PP and PSF™ RS3	0459 681 881
MXH™ 300/400w PP connection kit	0459 020 883
Water cooler, COOL 1	0462 300 880
Flow guard, COOL 1	0456 855 881
Trolley, 4-wheel	0462 151 880
Trolley bracket (without COOL 1)	0463 125 880
Trolley, 2-wheel for YardFeed	0460 564 880
Trolley, 4-wheel	0460 565 880
Bracket kit to assembly 4004i/5004i to the 2/4-wheel trolley 0460 564/565	0461 310 880
Stabilizer 4-wheel for counter balance	0460 946 880
Counter balance device	0458 705 880

**CONSUMABLES FOR PULSE MIG**

ESAB is offering a large range of consumables for welding of mild steel, stainless steel and aluminium. **Pulse MIG** is recommended as the method for positional welding from sheet metal up to medium thickness as it provides better control of the heat. The listed consumables combined with the pulse MIG synergic lines available from **U6** or **U82** are our recommendation for high productivity and quality welding.

**Mild Steel:**

- OK AristoRod 12.50/12.63 in Ø0.8 - Ø1.2 mm
- OK Autrod 12.51/12.64 in Ø0.8 - Ø1.2 mm

**Stainless Steel:**

- OK Autrod 308LSi in Ø0.8 - 1.6 mm
- OK Autrod 316LSi in Ø0.8 - 1.6 mm

**Aluminium:**

- OK Autrod 4043/4047 in Ø1.0 - 1.6 mm
- OK Autrod 5183/5356 in Ø1.0 - 1.6 mm

# Aristo® Mig 4004i Pulse

# Aristo® Feed 3004, U6/U8<sub>2</sub>

## Advanced Multi Process Inverter



**MIG**

**STICK**

**TIG**

**SAT-SWIFT ARC TRANSFER**

**PULSE/SUPER PULSE**





Aristo® Mig 4004i Pulse is a digital controlled MIG/MAG/MMA lightweight inverter based welding power source, designed for high productivity and quality welding applications.

This NEW series Aristo 4004i pulse builds on the already acclaimed welding performance with enhanced software and hardware, delivering increased response times, to provide superb starting characteristics and arc characteristics. Whether your welding Aluminium, Stainless steel or Mild steels. Performance has also been optimised for use with Co2 shielding gases.

Fan on demand cooling systems increase the welding time of the equipment. The cooling unit COOL 1 provides cooling of liquid-cooled torches to support great comfort to the welder. The cooling fans in the power source and the cooling system for the torch automatically turn off after 6.5 minutes inactivity, significantly reducing the idle time energy consumption.

This 4th generation inverter offers considerable improved efficiency with a high power factor. This gives you minimized energy consumption and will offer significant reductions in your energy cost with the same welding conditions.

Technology	Weight	Efficiency
Chopper	>149 kg	<70%
Inverter	46 kg	>85

## FEATURES

## BENEFITS

<b>NEW</b> Improved Arc Enhancements	Through hardware & software upgrades that improve start performance and welding with CO2. Feeder upgrades and new polished feed rolls for improved Aluminium feeding performance.
SuperPulse™	Advanced pulse functionality that reduces heat input and minimizes spatter (U82).
QSet™	An Intelligent welding system that monitors the welding arc and optimises welding parameters.
TrueArcVoltage™	Measures the correct arc voltage value at the contact tip, independent of interconnection cable length, return cable or welding torch assembly. (Valid with ESAB torches).
High Duty Cycle	For long runs and various applications ensuring high productivity 400 A at 60%
Wide mains input tolerance	380 - 460 V
Generator compatible	For on site use.
Robust Design	Heavy duty construction with added protection from moisture and dust.
Standby Function	For energy savings.
Improved Power Factor	0.95 and an efficiency of 89.5%
Memory	10 (U6) or 255 (U82) welding schedules.
Pre-programmed synergic lines	Up to 250 synergic lines (U82). To ensure optimum settings with a wide choice of materials, wire dimensions and gas combinations.
Customized synergic lines	For user customisation and flexibility.
Pre-flow, creep start, and hot start functions	Provides soft and more direct starts with less spatter.
Crater filling, adjustable burn-back time and post gas	For a defect-free weld, smooth finish and no cracks. Also extends the lifetime of the contact tip.

## APPLICATIONS

- Highly productive MIG/MAG and advanced MMA welding. Suitable for Aluminium, Stainless Steel, Mild Steel and Cored Wire.
- Typical market segments:
  - General Industrial Fabrication
  - Energy Generation
  - Windmills
  - Trucks Busses and Trailers
  - Trains & Railway Cars
  - Earthmoving and Mining Equipment
  - Mobile Machinery
  - Steel Sections
  - Shipbuilding/Offshore

## ARISTO MIG 4004i PULSE



## QSET™ - THE INTELLIGENCE WELDING SYSTEM WHICH SIMPLIFIES WELDING

QSet™ monitors the welding arc and optimizes welding parameters in dip transfer, just weld and the arc condition will be optimized within a few seconds. Then simply adjust the wire feed speed to suit the application and let QSet™ do the rest.

A robust fully enclosed design protects the welding wire from moisture, dust and other airborne contaminants.

Aristo® Feed 3004 is available with 2 operational solutions, the U6 panel and the U82 pendant.

A 7.5 m connection cable to provide a wider working range is available for the U82 pendant. Access for remote controls at the front of the feeder.

Adapter kit for PSF RS3 torches and MXH Push-Pull guns provide access to pre-programmed welding schedules from the torch (PSF RS3) or control of the wire feed speed from the PP guns (MXH 300/400w PP).

The feeder accept standard 200, 300 and 440 mm spools additional to MarathonPac™. (See Ordering information, Accessories).

## USER-FRIENDLY INTERFACE



1. Display
2. Soft pushbuttons (function keys)
3. Menu
4. Voltage setting
5. Wire feed speed or current setting

## LIVETIG™

The LiveTig™ start function electronically limits the start current by 12-15A is implemented to U6 and U82. Aristo® Mig 4004i Pulse combined with U6 or U82. offer a complete multi-process package supporting MMA, TIG, MIG/MAG and pulse MIG.

The package supports welding of mild steel and stainless steel in all processes and Aluminium in MMA, MIG/MAG and pulse MIG.

## SUPERPULSE™ (U82)

- Makes positional welding easier
- Allows welding with low heat input
- Provides uniform penetration
- Allows operator more control over welding speed
- TIG-looking weld appearance with MIG
- Extends working range with larger wire size
- Less sensitive to joint gap variations
- Less sensitive to unequal heat transfer



6. USB unit
7. Setting wheel
8. Large, bright display - ledgible when welding
9. Menu button
10. Setting wheel
11. Setting wheel
12. Function buttons
13. "Enter" button
14. Robust casing

For more details about Aristo® U82, see fact sheet XA00141820

## ARISTO FEED 3004 U6



## ARISTO FEED 3004 U82



## COOL A1

